



# ROCK BREAKER

## Excavator Attachment

The RAMRADE Rock Breaker has excellent hydraulic breakers with high frequency and impact energy. Built with high strength steel to withstand the toughest jobs and extreme conditions.



Specifications	Unit	100 Series	200 Series	300 Series	400 Series	430 Series	450 Series	500 Series
Excavator Size	Tonne	0.8 - 2.5	1.2 - 3.0	2.5 - 4.5	4.0 - 8.0	8.0 - 12.0	10.0 - 14.0	11.0 - 16.0
Weight	Kg	102	126	165	295	395	571	861
Required Oil Flow Range	LPM	15 - 25	20 - 30	25 - 50	40 - 70	50 - 90	60 - 100	80 - 110
Operating Pressure	Bar	90 - 120	90 - 120	90 - 120	110 - 140	120 - 150	130 - 160	150 - 170
	PSI	1,280 - 1,707	1,280 - 1,707	1,280 - 1,707	1,565 - 1,991	1,707 - 2,134	1,849 - 2,276	2,134 - 2,418
Impact Range	BPM	800 - 1,400	700 - 1,200	600 - 1,100	500 - 900	400 - 800	400 - 800	350 - 700
Chisel Diameter	mm	40	45	53	68	75	85	100

Specifications	Unit	600 Series	700 Series	800 Series	1000 Series	1200 Series	1300 Series	1500 Series
Excavator Size	Tonne	15 - 18	18 - 25	25 - 32	32 - 38	38 - 42	40 - 48	48 - 55
Weight	Kg	1,296	1,500	1,825	2,145	2,745	3,045	4,155
Required Oil Flow Range	LPM	90 - 120	100 - 150	120 - 180	150 - 210	180 - 240	200 - 260	210 - 290
Operating Pressure	Bar	150 - 170	160 - 180	160 - 180	160 - 180	160 - 180	160 - 180	160 - 180
	PSI	2,134 - 2,418	2,276 - 2,560	2,276 - 2,560	2,276 - 2,560	2,276 - 2,560	2,276 - 2,560	2,276 - 2,560
Impact Range	BPM	350 - 650	350 - 600	350 - 500	300 - 450	300 - 450	250 - 400	200 - 350
Chisel Diameter	mm	125	135	140	150	155	155	175

### KEY FEATURES

- Size Range to Suit 0.5 to 55 Tonne Excavators
- Designed for Extreme Conditions
- Noise Reduction Technology
- Fully Shock Absorbed
- Proven Durability
- Optional Auto-Greaser Available for Most Series